


# SHOP MANUAL CBF600S/SA/N/NA



CBF600N/NA/S/SA

### TYPE CODE

• Throughout this manual, the following abbreviations are used to identify individual model.

CODE	AREA TYPE	
ED	EUROPEAN DIRECT SALES (Italy, Germany, Portugal, Norway, Finland, Sweden, Denmark, Austria, Belgium Greece, Spain, Luxembourg, Netherlands, Switzerland, Russia, Eastern Europe)	
3ED	Germany	
Е	U.K., Ireland	
F	France, Belgium	

#### A Few Words About Safety

#### Service Information

The service and repair information contained in this manual is intended for use by qualified, professional technicians.

Attempting service or repairs without the proper training, tools, and equipment could cause injury to you or others. It could also damage the vehicle or create an unsafe condition.

This manual describes the proper methods and procedures for performing service, maintenance, and repairs. Some procedures require the use of specially designed tools and dedicated equipment. Any person who intends to use a replacement part, service procedure or a tool that is not recommended by Honda, must determine the risks to their personal safety and the safe operation of the vehicle.

If you need to replace a part, use genuine Honda parts with the correct part number or an equivalent part. We strongly recommend that you do not use replacement parts of inferior quality.

#### For Your Customer's Safety

Proper service and maintenance are essential to the customer's safety and the reliability of the vehicle. Any error or oversight while servicing a vehicle can result in faulty operation, damage to the vehicle, or injury to others.

#### For Your Safety

Because this manual is intended for the professional service technician, we do not provide warnings about many basic shop safety practices (e.g., Hot parts—wear gloves). If you have not received shop safety training or do not feel confident about your knowledge of safe servicing practice, we recommended that you do not attempt to perform the procedures described in this manual.

Some of the most important general service safety precautions are given below. However, we cannot warn you of every conceivable hazard that can arise in performing service and repair procedures. Only you can decide whether or not you should perform a given task.

#### **AWARNING**

Improper service or repairs can create an unsafe condition that can cause your customer or others to be seriously hurt or killed.

Follow the procedures and precautions in this manual and other service materials carefully.

#### **AWARNING**

Failure to properly follow instructions and precautions can cause you to be seriously hurt or killed.

Follow the procedures and precautions in this manual carefully.

#### Important Safety Precautions

Make sure you have a clear understanding of all basic shop safety practices and that you are wearing appropriate clothing and using safety equipment. When performing any service task, be especially careful of the following:

- Read all of the instructions before you begin, and make sure you have the tools, the replacement or repair parts, and the skills
  required to perform the tasks safely and completely.
- Protect your eyes by using proper safety glasses, goggles or face shields any time you hammer, drill, grind, pry or work around pressurized air or liquids, and springs or other stored-energy components. If there is any doubt, put on eye protection.
- Use other protective wear when necessary, for example gloves or safety shoes. Handling hot or sharp parts can cause severe burns or cuts. Before you grab something that looks like it can hurt you, stop and put on gloves.
- Protect yourself and others whenever you have the vehicle up in the air. Any time you lift the vehicle, either with a hoist or a jack, make sure that it is always securely supported. Use jack stands.

Make sure the engine is off before you begin any servicing procedures, unless the instruction tells you to do otherwise. This will help eliminate several potential hazards:

- · Carbon monoxide poisoning from engine exhaust. Be sure there is adequate ventilation whenever you run the engine.
- Burns from hot parts or coolant. Let the engine and exhaust system cool before working in those areas.
- . Injury from moving parts. If the instruction tells you to run the engine, be sure your hands, fingers and clothing are out of the way.

Gasoline vapors and hydrogen gases from batteries are explosive. To reduce the possibility of a fire or explosion, be careful when working around gasoline or batteries.

- · Use only a nonflammable solvent, not gasoline, to clean parts.
- Never drain or store gasoline in an open container.
- Keep all cigarettes, sparks and flames away from the battery and all fuel-related parts.

#### **HOW TO USE THIS MANUAL**

This service manual describes the service procedures for the CBF600N/ NA/S/SA

Follow the Maintenance Schedule (Section 3) recommendations to ensure that the vehicle is in peak operating condition.

Performing the first scheduled maintenance is very important. It compensates for the initial wear that occurs during the break-in period.

Sections 1 and 3 apply to the whole motorcycle. Section 2 illustrates procedures for removal/installation of components that may be required to perform service described in the following sections.

Section 4 through 20 describe parts of the motorcycle, grouped according to location.

Find the section you want on this page, then turn to the table of contents on the first page of the section.

Most sections start with an assembly or system illustration, service information and troubleshooting for the section. The subsequent pages give detailed procedure.

If you don't know the source of the trouble, go to section 22 Troubleshooting.

Your safety, and the safety of others, is very important. To help you make informed decisions we have provided safety messages and other information throughout this manual. Of course, it is not practical or possible to warn you about all the hazards associated with servicing this vehicle.

You must use your own good judgement.

You will find important safety information in a variety of forms including:

- · Safety Labels on the vehicle
- one of three signal words, DANGER, WARNING, or CAUTION. These signal words mean:

You WILL be KILLED or SERIOUSLY A DANGER HURT If you don't follow instructions.

AWARNING

You CAN be KILLED or SERIOUSLY HURT if you don't follow instructions.

ACAUTION

You CAN be HURT if you don't follow instructions.

· Instructions - how to service this vehicle correctly and safely.

As you read this manual, you will find information that is preceded by a NOTICE symbol. The purpose of this message is to help prevent damage to your vehicle, other property, or the environment.

ALL INFORMATION, ILLUSTRATIONS, DIREC-TIONS AND SPECIFICATIONS INCLUDED IN THIS PUBLICATION ARE BASED ON THE LAT-EST PRODUCT INFORMATION AVAILABLE AT THE TIME OF APPROVAL FOR PRINTING. HONDA MOTOR CO., LTD. RESERVES THE RIGHT TO MAKE CHANGES AT ANY TIME WITHOUT NOTICE AND WITHOUT INCURRING ANY OBLIGATION WHATSOEVER. NO PART OF THIS PUBLICATION MAY BE REPRODUCED WITHOUT WRITTEN PERMISSION. THIS MAN-UAL IS WRITTEN FOR PERSONS WHO HAVE ACQUIRED BASIC KNOWLEDGE OF MAINTE-NANCE ON HONDA MOTORCYCLES, MOTOR SCOOTERS OR ATVS.

> Honda Motor Co., Ltd. SERVICE PUBLICATION OFFICE

#### CONTENTS

[	GENERAL INFORMATION	1
ĺ	FRAME/BODY PANELS/EXHAUST SYSTEM	2
	MAINTENANCE	3
ENGINE AND DRIVE TRAIN	LUBRICATION SYSTEM	4
	FUEL SYSTEM	5 ·
	COOLING SYSTEM	6
	ENGINE REMOVAL/INSTALLATION	7
	CYLINDER HEAD/VALVES	8
	CLUTCH/GEARSHIFT LINKAGE	9
	ALTERNATOR/STARTER CLUTCH	10
	CRANKCASE/TRANSMISSION	11
	CRANKSHAFT/PISTON/CYLINDER	12
CHASSIS	FRONT WHEEL/SUSPENSION/ STEERING	13
	REAR WHEEL/SUSPENSION	14
	HYDRAULIC BRAKE	15
	ANTI-LOCK BRAKE SYSTEM (ABS)	16
ELECTRICAL	BATTERY/CHARGING SYSTEM	17
	IGNITION SYSTEM	18
	ELECTRIC STARTER	19
	LIGHTS/METERS/SWITCHES	20
	WIRING DIAGRAMS	21
	TROUBLESHOOTING	22
	INDEX	23

## **SYMBOLS**

The symbols used throughout this manual show specific service procedures. If supplementary information is required pertaining to these symbols, it would be explained specifically in the text without the use of the symbols.

	Replace the part(s) with new one(s) before assembly.	
	Use recommended engine oil, unless otherwise specified.	
	Use molybdenum oil solution (mixture of the engine oil and molybdenum grease in a ratio of 1: 1).	
GREASE	Use multi-purpose grease (Lithium based multi-purpose grease NLGI #2 or equivalent).	
	Use molybdenum disulfide grease (containing more than 3% molybdenum disulfide, NLGI #2 o equivalent).	
WW.	Example: Molykote® BR-2 plus manufactured by Dow Corning U.S.A.	
	Multi-purpose M-2 manufactured by Mitsubishi Oil, Japan	
=	Use molybdenum disulfide paste (containing more than 40% molybdenum disulfide, NLGI #2 o equivalent).	
-	Example: Molykote® G-n Paste manufactured by Dow Corning U.S.A.	
MEN	Honda Moly 60 (U.S.A. only)	
	Rocol ASP manufactured by Rocol Limited, U.K.	
	Rocol Paste manufactured by Sumico Lubricant, Japan	
- TISM	Use silicone grease.	
LOCK	Apply a locking agent. Use a middle strength locking agent unless otherwise specified.	
SEALL	Apply sealant.	
RLUID FLUID	Use DOT 4 brake fluid. Use the recommended brake fluid unless otherwise specified.	
FORK	Use Fork or Suspension Fluid.	

# 1. GENERAL INFORMATION


SERVICE RULES 1-2	FRONT WHEEL/SUSPENSION/STEERING SPECIFICATIONS1-10	
MODEL IDENTIFICATION 1-3	REAR WHEEL/SUSPENSION	
GENERAL SPECIFICATIONS 1-5	SPECIFICATIONS1-10	
LUBRICATION SYSTEM	HYDRAULIC BRAKE SPECIFICATIONS1-11	
SPECIFICATIONS1-7	BATTERY/CHARGING SYSTEM SPECIFICATIONS1-11	
FUEL SYSTEM 1-7		
COOLING SYSTEM SPECIFICATIONS 1-7	IGNITION SYSTEM SPECIFICATIONS1-11	
CYLINDER HEAD/VALVES SPECIFICATIONS	ELECTRIC STARTER SPECIFICATIONS1-11	
	LIGHTS/METERS/SWITCHES SPECIFICATIONS1-12	
CLUTCH/GEARSHIFT LINKAGE SPECIFICATIONS1-8		
ALTERNATOR/CTARTER CLUTCH	STANDARD TORQUE VALUES1-13	
SPECIFICATIONS 1-8	ENGINE & FRAME TORQUE VALUES1-13	
CRANKCASE/TRANSMISSION SPECIFICATIONS	LUBRICATION & SEAL POINTS1-20	
	CABLE & HARNESS ROUTING1-24	
CRANKSHAFT/PISTON/CYLINDER SPECIFICATIONS1-9	EMISSION CONTROL SYSTEMS1-46	

#### SERVICE RULES

- Use genuine Honda or Honda-recommended parts and lubricants or their equivalents. Parts that don't meet Honda's design specifications may cause damage to the motorcycle.
- 2. Use the special tools designed for this product to avoid damage and incorrect assembly.
- Use only metric tools when servicing the motorcycle. Metric bolts, nuts and screws are not interchangeable with English fasteners.
- 4. Install new gaskets, O-rings, cotter pins, and lock plates when reassembling.
- 5. When tightening bolts or nuts, begin with the larger diameter or inner bolt first. Then tighten to the specified torque diagonally in incremental steps unless a particular sequence is specified.
- 6. Clean parts in cleaning solvent upon disassembly. Lubricate any sliding surfaces before reassembly.
- 7. After reassembly, check all parts for proper installation and operation.
- 8. Route all electrical wires as show in the Cable and Harness Routing (page 1-24).

# MODEL IDENTIFICATION

CBF600S shown:



CBF600N shown:

